



Classical Timing Belts

TIMING / SYNCHRONOUS BELTS

PIX-X'act[®] CT CLASSICAL TIMING BELTS



XL	5.080	130XL - 450XL
L	9.525	124L - 720L
H	12.700	230H - 1700H

BELT DESIGNATION:

PIX-X'act[®] CT 270 XL XL 025
PIX-X'act[®] CT 270 XL XL 025

270 XL 025		
270	XL	025
↓	↓	↓
Pitch Length 27"	Section (Tooth pitch 5.080 mm)	Belt Width 0.25"

Note : Maximum sleeve width is available up to 450 mm

PIX-X'act[®] HTD TIMING BELTS



5M	5.00	330 5M - 2100 5M
8M	8.00	424 8M - 3600 8M
14M	14.00	966 14M - 3850 14M

BELT DESIGNATION:

PIX-X'act[®] HTD 800 8M 8M 30
PIX-X'act[®] HTD 800 8M 8M 30

800 8M 30		
800	8M	30
↓	↓	↓
Pitch Length 800 mm	Section (Tooth pitch 8.0 mm)	Belt Width 30 mm

Note : Maximum sleeve width is available up to 450 mm

PIX-X'act[®] STD TIMING BELTS



S5M	5.00	STD S 5M 375 - STD S 5M 2525
S8M	8.00	STD S 8M 376 - STD S 8M 2600

BELT DESIGNATION:

PIX-X'act[®] STD S 5M 650 S 5M 15
PIX-X'act[®] STD S 5M 650 S 5M 15

STD 150 S 5M 650		
STD 150	S 5M	650
↓	↓	↓
Belt Top Width 15 mm	Section (Tooth pitch 5.0 mm)	Pitch Length 650 mm

Note : Maximum sleeve width is available up to 450 mm

PIX-X'act[®] TOP COAT TIMING BELTS



FEATURES:

- Timing belt with profile top rubber
- Hardness (Shore A 45 & 75) provides excellent cushioning with elasticity

RANGE: Classical Timing Belt "L" section

Other sections can be provided on request.

APPLICATIONS:

- Packaging industry