



# SPA V-Pulley (taper-lock)

Pulley (dw)	Grooves	Bush	d2 Max	Type	L	b	d3	d1	d	App. Kg
63	1	1008				20			69	
63	2	1008				35			69	
67	1	1108				20			73	
67	2	1108				35			73	
71	1	1108				20			79	
71	2	1108				35			79	
75	1	1108	28			20			80.6	0.50
	2	1108	28			35			80.6	0.70
80	1	1210	32			20			85.6	0.50
	2	1210	32			35			85.6	0.75
	3	1210	32			50			85.6	0.95
85	1	1210	32			20			90.6	0.60
	2	1210	32			35			90.6	0.80
	3	1210	32			50			90.6	1.00
90	1	1210	32			20			95.6	0.70
	2	1610	42			35			95.6	0.80
	3	1610	42			50			95.6	1.05
	4	1615	42			65			95.6	1.35
95	1	1210	32			20			100.6	0.80
	2	1610	42			35			100.6	1.00
	3	1610	42			50			100.6	1.20
	4	1615	42			65			100.6	1.50
100	1	1610	42			20			105.6	0.85
	2	1610	42			35			105.6	1.00
	3	1610	42			50			105.6	1.40
	4	1615	42			65			105.6	1.80
	5	1615	42			80			105.6	2.20
	6	1615	42			95			105.6	2.35
106	1	1610	42			20			111.6	1.00
	2	1610	42			35			111.6	1.30
	3	1610	42			50			111.6	1.50
	4	2012	50			65			111.6	1.70
	5	2012	50			80			111.6	2.10
	6	2012	50			95			111.6	2.40
112	1	1610	42			20			117.6	1.05
	2	1610	42			35			117.6	1.35
	3	2012	50			50			117.6	1.80
	4	2012	50			65			117.6	2.00
	5	2012	50			80			117.6	2.50
	6	2012	50			95			117.6	2.70
118	1	1610	42			2			123.6	1.20
	2	1610	42			4			123.6	1.60
	3	2012	50			5			123.6	1.85
	4	2012	50			5			123.6	2.20
	5	2012	50			5			123.6	2.70
	6	2012	50			4			123.6	3.00
125	1	1610	42			20			130.6	1.35
	2	1610	42			35			130.6	1.85
	3	2012	50			50			130.6	2.25
	4	2012	50			65			130.6	2.70
	5	2012	50			80			130.6	3.10
	6	2012	50			95			130.6	3.50

# SPA V-Pulley (taper-lock)



Pulley (dw)	Grooves	Bush	d2 Max	Type	L	b	d3	d1	d	App. Kg
132	1	1610	42			20			137.6	1.60
	2	2012	50			35			137.6	2.10
	3	2012	50			50			137.6	2.55
	4	2517	60			65			137.6	2.80
	5	2517	60			80			137.6	3.30
	6	2517	60			95			137.6	3.80
140	1	1610	42			20			145.6	1.80
	2	2012	50			35			145.6	2.50
	3	2517	60			50			145.6	2.80
	4	2517	60			65			145.6	3.80
	5	2517	60			80			145.6	4.00
	6	2517	60			95			145.6	4.65
150	1	1610	42			20			155.6	2.20
	2	2012	50			35			155.6	3.00
	3	2517	60			50			155.6	3.55
	4	2517	60			65			155.6	4.10
	5	2517	60			80			155.6	4.90
	6	2517	60			95			155.6	5.20
160	1	1610	42			20			165.6	1.85
	2	2012	50			35			165.6	3.50
	3	2517	60			50			165.6	4.40
	4	2517	60			65			165.6	5.10
	5	2517	60			80			165.6	5.50
	6	2517	60			95			165.6	6.20
180	1	1610	42			20			185.6	2.00
	2	2012	50			35			185.6	3.80
	3	2517	60			50			185.6	6.00
	4	2517	60			65			185.6	6.65
	5	3020	75			80			185.6	6.80
	6	3020	75			95			185.6	9.30
190	2	2012				35			195.5	4.40
	3	2517				50			195.5	5.50
200	1	2012	50			20			205.6	3.00
	2	2517	60			35			205.6	4.40
	3	2517	60			50			205.6	5.20
	4	3020	75			65			205.6	8.30
	5	3020	75			80			205.6	8.90
	6	3020	75			95			205.6	9.80
212	3	2517	60			50			217.6	6.00
224	1	2012	50			20			229.6	3.25
	2	2517	60			35			229.6	5.25
	3	2517	60			50			229.6	6.20
	4	3020	75			65			229.6	11.20
	5	3020	75			80			229.6	12.10
	6	3020	75			95			229.6	13.40
250	1	2012	50			20			255.6	3.80
	2	2517	60			35			255.6	5.80
	3	2517	60			50			255.6	6.55
	4	3020	75			65			255.6	9.70
	5	3020	75			80			255.6	10.50
	6	3020	75			95			255.6	11.70



# SPA V-Pulley (taper-lock)

Pulley (dw)	Grooves	Bush	d2 Max	Type	L	b	d3	d1	d	App. Kg
280	1	2012	50			20			285.6	4.70
	2	2517	60			35			285.6	6.40
	3	2517	60			50			285.6	8.90
	4	3020	75			65			285.6	10.40
	5	3535	90			80			285.6	15.10
	6	3535	90			95			285.6	16.70
315	1	2012	50			20			320.6	4.90
	2	2517	60			35			320.6	7.50
	3	3020	75			50			320.6	11.80
	4	3020	75			65			320.6	15.50
	5	3535	90			80			320.6	17.30
	6	3535	90			95			320.6	18.90
355	1	2012	50			20			360.6	5.50
	2	2517	60			35			360.6	8.80
	3	3020	75			50			360.6	12.20
	4	3020	75			65			360.6	13.50
	5	3535	90			80			360.6	20.20
	6	3535	90			95			360.6	21.00
400	1	2012	50			20			405.6	5.91
	2	2517	60			35			405.6	9.35
	3	3020	75			50			405.6	13.32
	4	3020	75			65			405.6	15.45
	5	3535	90			80			405.6	22.09
	6	3535	90			95			405.6	24.25
450	1	2012	50			20			455.6	6.77
	2	2517	60			35			455.6	10.62
	3	3020	75			50			455.6	15.11
	4	3020	75			65			455.6	17.94
	5	3535	90			80			455.6	24.65
	6	3535	90			95			455.6	27.31
500	2	2517	60			35			505.6	12.11
	3	3020	75			50			505.6	17.09
	4	3020	75			65			505.6	20.07
	5	3535	90			80			505.6	27.33
	6	3535	90			95			505.6	30.55
630	2	3020	75			35			635.6	17.80
	3	3020	75			50			635.6	22.68
	4	3535	90			65			635.6	31.17
	5	3535	90			80			635.6	35.31
	6	4040	100			95			635.6	47.72
800	3	3535	90			50			805.6	34.76
	4	3535	90			65			805.6	41.11
	5	4040	100			80			805.6	54.54
	6	4040	100			95			805.6	59.75
1000	3	3535	90			50			1005.6	45.99
	4	4040	100			65			1005.6	63.94
	5	4545	110			80			1005.6	76.41
	6	4545	110			95			1005.6	85.40