





British Standard Taper Locks



10B-1-2 Taper Lock		Teeth	de	dp	Simplex				Duplex					
					dm	A	Bush	Type	App. Kg	dm	A	Bush	Type	App. Kg
		13	73.2	66.32	47	22.23	1008	1	0.23					
		14	78	71.44	52	22.23	1108	1	0A					
		15	83.2	76.36	60	25.40	1210	1	0.32	-	25.4	1210	0A	0.48
		16	88.3	81.37		25.40	1210	1	0.37	-	25.4	1610	0A	0A
		17	93.3	86.39	71	25.40	1610	1	0.41	-	25.4	1610	0A	0.57
		18	98.3	91.42		25.40	1610	1	0.51		25.4	1610	0A	0A
		19	103.3	96.45	75	25.40	1610	1	0.64	-	25.4	1610	0A	0.71
		20	108.4	101.5		25.40	1610	1	0.68		25.4	1610	0A	0A
		21	113.4	106.5	76	25.40	1610	1	0.73	-	25.4	1610	0A	0.86
		22	118.4	111.6		25.40	1610	1	0.78	-	25.4	1610	0A	0A
		23	123.5	116.6	76	25.40	1610	1	0.82	-	25.4	1610	0A	0.98
		24	128.5	121.6		25.40	1610	1	0.91	90	31.75	2012	0A	0A
		25	133.6	126.7	90	31.75	2012	1	1.09	90	31.75	2012	0A	3.40
		26	138.6	131.7	90	31.75	2012	1	1.14	90	31.75	2012	0A	0A
		27	143.6	136.8	90	31.75	2012	1	1.18	90	31.75	2012	0A	3.50
		28	148.7	141.8	90	31.75	2012	1	1.29	90	31.75	2012	0A	0A
		29	153.7	146.8	0A	0A	2012	1	0A					
		30	158.8	151.9	90	31.75	2012	1	1.41	90	31.75	2012	0A	3.92
		32	168.9	162	90	31.75	2012	1	1.63					
		38	199.1	192.2	90	31.75	2012	1	2.22	90	31.75	2012	0A	5.68
		45	236	227.6	90	31.75	2012	1	2.95					
		57	296.6	288.2	90	31.75	2012	1	4.59	0A	0A	0A	0A	0A
		76	392.5	384.2	110	31.75	2012	1	8.31	0A	0A	0A	0A	0A
		95	488.5	480.1	110	44.45	2517	1	12.76					
		114	584.5	576.1				1						



Pinions	mm
Tooth Radius r3	
Radius Width C	
Tooth Width B1	9.1
Chain	mm
Pitch	5.88
Inside	9.65
Roller ø	10.2



SPROCKETS

Bearings & Power Transmission Pty Ltd | www.bpt.net.au