




Pulleys

Contents

PULLEYS

Timing Pulley	158
8M HTD Timing Pulley	159
14M HTD Timing Pulley	161
 Mi-Lock Pulley	 163
Mi-Lock V-Pulleys	163
Mi-Lock No 1 Bushes	163
Mi-Lock No 2 Bushes	163
 V-Belt Pulley	 164
SPA Pulley (taper lock)	166
SPB Pulley (taper lock)	169
SPC Pulley (taper lock)	172
SPZ Pulley (taper lock)	175

HTD Timing Pulley

Bearings & Power Transmissions carries a large range of Taper Locked, HTD Timing Pulley's in 8M and 14M pitch.

Timing Belts are measured by:

38	8M	50
Teeth	Pitch	Width




Type 3F




Type 3A



Type 4F




Type 4



Type 5F



Type 7A




Type 7W



Type 8F




Type 8W




Type 8WF




Type 8A



Type 9W



Type 9WF



Type 9A

HTD Timing Pulley



8M HTD Timing Pulley												
Size	Teeth	Type	Mat	Bush	Outside Dia.	Hub Dia.	K	W	L	d3	D1	Max. Bore
22-8M-20	22		GG	1008	54.65	60.0		28.0				25
22-8M-30	22		GG	1008	54.65	60.0		38.0				25
24-8M-20	24		GG	1108	59.75	66.0		28.0				28
24-8M-30	24		GG	1108	59.75	66.0		38.0				28
26-8M-20	26		GG	1108	64.84	71.0		28.0				28
26-8M-30	26		GG	1108	64.84	71.0		38.0				28
28-8M-20	28		GG	1108	70.08	75.0		28.0				28
28-8M-30	28		GG	1210	70.08	75.0		38.0				35
28-8M-50	28		GG	1210	70.08	75.0		60.0				35
30-8M-20	30		GG	1108	75.13	83.0		28.0				28
30-8M-30	30		GG	1615	75.13	83.0		38.0				42
30-8M-50	30		GG	1615	75.13	83.0		60.0				42
32-8M-20	32		GG	1610	80.16	87.0		28.0				42
32-8M-30	32		GG	1615	80.16	87.0		38.0				42
32-8M-50	32		GG	1615	80.16	87.0		60.0				42
34-8M-20	34		GG	1610	85.22	91.0		28.0				42
34-8M-30	34		GG	1610	85.22	91.0		28.0				42
34-8M-50	34		GG	1615	85.22	91.0		60.0				42
34-8M-85	34		GG	1615	85.22	91.0		95.0				42
36-8M-20	36		GG	1610	90.30	98.5		28.0				42
36-8M-30	36		GG	1615	90.30	98.5		38.0				42
36-8M-50	36		GG	1615	95.39	103.0		60.0				42
36-8M-85	36		GG	1615	90.35	98.5		95.0				42
38-8M-20	38		GG	1610	95.39	103.0		28.0				42
38-8M-30	38		GG	1615	95.39	103.0		38.0				42
38-8M-50	38		GG	1615	95.39	103.0		60.0				42
38-8M-85	38		GG	1615	95.39	103.0		95.0				42
40-8M-20	40		GG	1610	100.49	106.0		28.0				42
40-8M-30	40		GG	1615	100.49	106.0		38.0				42
40-8M-50	40		GG	2012	100.49	106.0		60.0				50
40-8M-85	40		GG	2012	100.49	106.0		95.0				50
44-8M-20	44		GG	2012	110.67	119.0		28.0				50
44-8M-30	44		GG	2012	110.67	119.0		38.0				50
44-8M-50	44		GG	2012	110.67	119.0		60.0				50
44-8M-85	44		GG	2012	110.67	119.0		95.9				50

HTD Timing Pulley

8M HTD Timing Pulley continued

Size	Teeth	Type	Mat	Bush	Outside Dia.	Hub Dia.	K	W	L	d3	D1	Max. Bore
48-8M-20	48		GG	2012	120.86	127.0		28.0		96		50
48-8M-30	48		GG	2012	120.86	127.0		38.0				50
48-8M-50	48		GG	2012	120.86	127.0		60.0				50
48-8M-85	48		GG	2517	120.86	127.0		95.0				60
56-8M-20	56		GG	2012	141.23	148.0		28.0		110		50
56-8M-30	56		GG	2012	141.23	148.0		38.0				50
56-8M-50	56		GG	2517	141.23	148.0		60.0				60
56-8M-85	56		GG	2517	120.86	127.0		95.0				60
64-8M-20	64		GG	2012	161.60	168.0		28.0		110		50
64-8M-30	64		GG	2517	161.60	168.0		38.0		125		60
64-8M-50	64		GG	2517	161.60	168.0		60.0				60
64-8M-85	64		GG	2517	161.60	168.0		95.0				60
72-8M-20	72		GG	2012	181.97	192.0		28.0		110		50
72-8M-30	72		GG	2517	181.97	192.0		38.0		125		60
72-8M-50	72		GG	2517	181.97	192.0		60.0		125		60
72-8M-85	72		GG	3020	181.97	192.0		95.0				75
80-8M-20	80		GG	2012	202.35			28.0		110		50
80-8M-30	80		GG	2517	202.35			38.0		125		60
80-8M-50	80		GG	3020	202.35			60.0				75
80-8M-85	80		GG	3020	202.35			95.0				75
90-8M-20	90		GG	2012	227.81			28.0		110		50
90-8M-30	90		GG	2517	227.81			38.0		125		60
90-8M-50	90		GG	3020	227.81			60.0		170		75
90-8M-85	90		GG	3020	227.81			95.0		170		75
112-8M-30	112		GG	2517	283.83			38.0		125		60
112-8M-50	112		GG	3020	283.83			60.0		170		75
112-8M-85	112		GG	3020	283.83			95.0		170		75
144-8M-30	144		GG	2517	365.32			38.0		125		60
144-8M-50	144		GG	3020	365.32			60.0		170		75
144-8M-85	144		GG	3525	365.32			95.0		190		90
168-8M-50	168		GG	3525	426.44			60.0		190		90
168-8M-85	168		GG	3525	426.44			95.0		190		90
192-8M-50	192		GG	3525	487.55			60.0		190		90
192-8M-85	192		GG	3525	487.55			95.0		190		90

HTD Timing Pulley

14M HTD Timing Pulley												
Size	Teeth	Type	Mat	Bush	Outside Dia.	Hub Dia.	K	W	L	d3	D1	Max. Bore
28-14M-40	28		GG	2012	122.12	127		54				50
28-14M-55	28		GG	2012	122.12	127		70				50
28-14M-85	28		GG	2517	122.12	127		102				60
28-14M-115	28		GG	2517	122.12	127		133				60
29-14M-40	29		GG	2012	126.57	138		54				50
29-14M-55	29		GG	2012	126.57	138		70				50
29-14M-85	29		GG	2517	126.57	138		102				60
29-14M-115	29		GG	2517	126.57	138		133				60
30-14M-40	30		GG	2012	130.99	138		54				50
30-14M-55	30		GG	2517	130.99	138		70				60
30-14M-85	30		GG	2517	130.99	138		102				60
30-14M-115	30		GG	2517	130.99	138		133				60
32-14M-40	32		GG	2012	139.88	154		54				50
32-14M-55	32		GG	2517	139.88	154		70				60
32-14M-85	32		GG	2517	139.88	154		102				60
32-14M-115	32		GG	2517	139.88	154		133				60
34-14M-40	34		GG	2517	148.79	160		54				60
34-14M-55	34		GG	2517	146.79	160		70				60
34-14M-85	34		GG	2517	146.79	160		102				60
34-14M-115	34		GG	2517	146.79	160		133				60
36-14M-40	36		GG	2517	157.68	168		54				60
36-14M-55	36		GG	2517	157.68	168		70				60
36-14M-85	36		GG	3020	157.68	168		102				75
36-14M-115	36		GG	3020	157.68	168		133				75
38-14M-40	38		GG	2517	166.6	183		54				60
38-14M-55	38		GG	2517	166.6	183		70				60
38-14M-85	38		GG	3020	166.6	183		102				75
38-14M-115	38		GG	3020	166.6	183		133				75
40-14M-40	40		GG	2517	175.49	188		54				60
40-14M-55	40		GG	2517	175.49	188		70				60
40-14M-85	40		GG	3020	175.49	188		102				75
40-14M-115	40		GG	3020	175.49	188		133				75
44-14M-40	44		GG	3020	193.28	211		54				75
44-14M-55	44		GG	3020	293.28	211		70				75
44-14M-85	44		GG	3030	293.28	211		102				75
44-14M-115	44		GG	3030	293.28	211		133				75
48-14M-40	48		GG	3020	211.11	226		54				75
48-14M-55	48		GG	3020	211.11	226		70				75
48-14M-85	48		GG	3030	211.11	226		102				75
48-14M-115	48		GG	3030	211.11	226		133				75

HTD Timing Pulley

14M HTD Timing Pulley continued

Size	Teeth	Type	Mat	Bush	Outside Dia.	Hub Dia.	K	W	L	d3	D1	Max. Bore
56-14M-40	56		GG	3020	246.76	256		54		170		75
56-14M-55	56		GG	3020	246.76	256		70		170		75
56-14M-85	56		GG	3535	246.76	256		102		190		90
56-14M-115	56		GG	3535	246.76	256		133				90
64-14M-40	64		GG	3020	282.41	296		54		170		75
64-14M-55	64		GG	3020	282.41	296		70		170		75
64-14M-85	64		GG	3525	282.41	296		102		190		90
64-14M-115	64		GG	3535	282.41	296		133		190		90
72-14M-40	72		GG	3020	318.06			54		170		75
72-14M-55	72		GG	3020	318.06			70		170		75
72-14M-85	72		GG	3525	318.06			102		190		90
72-14M-115	72		GG	3535	318.06			133		190		90
80-14M-40	80		GG	3535	353.71			133		190		90
80-14M-55	80		GG	3020	353.71			70		170		75
80-14M-85	80		GG	3525	353.71			102		190		90
80-14M-115	80		GG	3535	353.71			133		190		90
90-14M-40	90		GG	3020	398.28			54		170		75
90-14M-55	90		GG	3020	398.28			70		170		75
90-14M-85	90		GG	3525	398.28			102		190		90
90-14M-115	90		GG	3535	398.28			133		190		90
112-14M-40	112		GG	3020	496.32			54		170		75
112-14M-55	112		GG	3020	496.32			70		170		75
112-14M-85	112		GG	3020	496.32			70		170		75
112-14M-115	112		GG	3535	496.32			133		190		90
144-14M-40	144		GG	3020	638.92			54		170		75
144-14M-55	144		GG	3020	638.92			70		170		75
144-14M-85	144		GG	3525	638.92			102		190		90
144-14M-115	144		GG	4040	638.92			133		230		100
168-14M-40	168		GG	3020	745.87			54		170		75
168-14M-55	168		GG	3020	745.87			70		170		75
168-14M-85	168		GG	3525	745.87			102		190		90
168-14M-115	168		GG	4040	745.87			133		230		100
192-14M-40	192		GG	3020	852.82			54		170		75
192-14M-55	192		GG	3020	852.82			70		170		75
192-14M-85	192		GG	4040	852.82			102		230		100
192-14M-115	192		GG	4040	852.82			133		230		100
216-14M-40	216		GG	3020	959.76			54		170		75
216-14M-55	216		GG	0A	959.76							
216-14M-85	216		GG	4040	959.76			102		230		100
216-14M-115	216		GG	4040	959.76			133		230		100

Mi-Lock Pulleys and Bushes



MI-LOCK V-PULLEYS					
Finer Part	Pulley Size Pitch A	Pulley Size Pitch B	Outside Diamter	Mass Kg	Suitable Bush & Size
71MM-MI-LOCK	71MM	81MM	88MM	0.42	No 1
75MM-MI-LOCK	75MM	85MM	92MM	0.47	No 1
80MM-MI-LOCK	80MM	90MM	97MM	0.53	No 1
85MM-MI-LOCK	85MM	95MM	102MM	0.62	No 1
90MM-MI-LOCK	90MM	100MM	107MM	0.72	No 1
95MM-MI-LOCK	95MM	105MM	111MM	0.80	No 1
100MM-MI-LOCK	100MM	110MM	117MM	0.91	No 1
106MM-MI-LOCK	106MM	116MM	123MM	1.02	No 1
112MM-MI-LOCK	112MM	122MM	129MM	0.98	No 1
118MM-MI-LOCK	118MM	128MM	135MM	1.05	No 1
125MM-MI-LOCK	125MM	135MM	142MM	1.17	No 1
132MM-MI-LOCK	132MM	142MM	149MM	1.28	No 1
140MM-MI-LOCK	140MM	150MM	157MM	1.49	No 2
150MM-MI-LOCK	150MM	160MM	167MM	1.61	No 2
160MM-MI-LOCK	160MM	170MM	177MM	1.75	No 2
180MM-MI-LOCK	180MM	190MM	197MM	2.03	No 2
200MM-MI-LOCK	200MM	209MM	216MM	2.38	No 2
224MM-MI-LOCK	224MM	233MM	240MM	3.34	No 2
250MM-MI-LOCK	250MM	259MM	266MM	4.22	No 2
280MM-MI-LOCK	280MM	289MM	296MM	4.34	No 2
315MM-MI-LOCK	315MM	324MM	331MM	4.45	No 2
355MM-MI-LOCK	355MM	364MM	371MM	4.94	No 2
400MM-MI-LOCK	400MM	409MM	416MM	7.51	No 2
450MM-MI-LOCK	450MM	459MM	466MM	9.05	No 2

MI-LOCK NO 1 BUSHES	
SIZE	IMPERIAL
10MM	1/2"
12MM	5/8"
14MM	11/16"
15MM	3/4"
16MM	13/16"
18MM	7/8"
19MM	15/16"
20MM	1"
22MM	1-1/8"
24MM	1-1/16"
25MM	
28MM	

Constructed from cast iron, this range of Mi-Lock pulleys can handle both A and B section belts (NB. Pitch circle sizing is based on PCD of A section).

Mi-Lock pulleys can be together to make multi-groove pulleys of varying sections and sizes allows you to reduce your total inventory.

MI-LOCK NO 2 BUSHES	
SIZE	IMPRERIAL
16MM	1/2"
18MM	9/16"
19MM	5/8"
20MM	11/16"
22MM	3/4"
24MM	13/16"
25MM	7/8"
28MM	15/16"
30MM	1"
32MM	1-1/16"
35MM	1-1/8"
38MM	1-3/16"
42MM	1-1/4"
	1-5/16"
	1-3/8"
	1-7/16"
	1-1/2"
	1-9/16"

BPT stock a range of quality V-Belt Pulleys. Constructed from cast iron, each pulley is Taper Locked to accommodate a range of shaft sizes.


BPT pulleys under go stringent balancing tests, to ensure each pulley functions efficiently. The pulleys are finished in a black coating; this acts as a primer to help protect the pulleys from environmental factors.

Bearings & Power Transmissions carry a range of Taper Lock V-Belt Pulleys in:


SPZ, SPA, SPB and SPC.

Groove Dimensions

Size	dp		f	e	g	h	b
SPZ	<80	34	8	12	9.7	9	2
	>80	38			9.9		
SPA	<118	34	10	15	12.7	11	2.75
	>118	38			12.9		
SPB	<190	34	12.5	19	16.1	14	3.5
	>190	38			16.4		
SPC	<315	34	17	25.5	21.9	19	4.8
	>315	38			22.3		




V-Belt Pulley Selection Table




V-Pulley

V-Belt Pulley




Type 1




Type 2




Type 3




Type 4




Type 5




Type 6




Type 7




Type 8



Type 9



Type 10



Type 11



Bearings &
Power Transmission Pty Ltd
(Phone) 07 4636 0522

SPA V-Pulley (taper-lock)

PULLEYS

Pulley (dw)	Grooves	Bush	d2 Max	Type	L	b	d3	d1	d	App. Kg
63	1	1008				20			69	
63	2	1008				35			69	
67	1	1108				20			73	
67	2	1108				35			73	
71	1	1108				20			79	
71	2	1108				35			79	
75	1	1108	28			20			80.6	0.50
	2	1108	28			35			80.6	0.70
80	1	1210	32			20			85.6	0.50
	2	1210	32			35			85.6	0.75
	3	1210	32			50			85.6	0.95
85	1	1210	32			20			90.6	0.60
	2	1210	32			35			90.6	0.80
	3	1210	32			50			90.6	1.00
90	1	1210	32			20			95.6	0.70
	2	1610	42			35			95.6	0.80
	3	1610	42			50			95.6	1.05
	4	1615	42			65			95.6	1.35
95	1	1210	32			20			100.6	0.80
	2	1610	42			35			100.6	1.00
	3	1610	42			50			100.6	1.20
	4	1615	42			65			100.6	1.50
100	1	1610	42			20			105.6	0.85
	2	1610	42			35			105.6	1.00
	3	1610	42			50			105.6	1.40
	4	1615	42			65			105.6	1.80
	5	1615	42			80			105.6	2.20
	6	1615	42			95			105.6	2.35
106	1	1610	42			20			111.6	1.00
	2	1610	42			35			111.6	1.30
	3	1610	42			50			111.6	1.50
	4	2012	50			65			111.6	1.70
	5	2012	50			80			111.6	2.10
	6	2012	50			95			111.6	2.40
112	1	1610	42			20			117.6	1.05
	2	1610	42			35			117.6	1.35
	3	2012	50			50			117.6	1.80
	4	2012	50			65			117.6	2.00
	5	2012	50			80			117.6	2.50
	6	2012	50			95			117.6	2.70
118	1	1610	42			2			123.6	1.20
	2	1610	42			4			123.6	1.60
	3	2012	50			5			123.6	1.85
	4	2012	50			5			123.6	2.20
	5	2012	50			5			123.6	2.70
	6	2012	50			4			123.6	3.00
125	1	1610	42			20			130.6	1.35
	2	1610	42			35			130.6	1.85
	3	2012	50			50			130.6	2.25
	4	2012	50			65			130.6	2.70
	5	2012	50			80			130.6	3.10
	6	2012	50			95			130.6	3.50

SPA V-Pulley (taper-lock)



Pulley (dw)	Grooves	Bush	d2 Max	Type	L	b	d3	d1	d	App. Kg
132	1	1610	42			20			137.6	1.60
	2	2012	50			35			137.6	2.10
	3	2012	50			50			137.6	2.55
	4	2517	60			65			137.6	2.80
	5	2517	60			80			137.6	3.30
	6	2517	60			95			137.6	3.80
140	1	1610	42			20			145.6	1.80
	2	2012	50			35			145.6	2.50
	3	2517	60			50			145.6	2.80
	4	2517	60			65			145.6	3.80
	5	2517	60			80			145.6	4.00
	6	2517	60			95			145.6	4.65
150	1	1610	42			20			155.6	2.20
	2	2012	50			35			155.6	3.00
	3	2517	60			50			155.6	3.55
	4	2517	60			65			155.6	4.10
	5	2517	60			80			155.6	4.90
	6	2517	60			95			155.6	5.20
160	1	1610	42			20			165.6	1.85
	2	2012	50			35			165.6	3.50
	3	2517	60			50			165.6	4.40
	4	2517	60			65			165.6	5.10
	5	2517	60			80			165.6	5.50
	6	2517	60			95			165.6	6.20
180	1	1610	42			20			185.6	2.00
	2	2012	50			35			185.6	3.80
	3	2517	60			50			185.6	6.00
	4	2517	60			65			185.6	6.65
	5	3020	75			80			185.6	6.80
	6	3020	75			95			185.6	9.30
190	2	2012				35			195.5	4.40
	3	2517				50			195.5	5.50
200	1	2012	50			20			205.6	3.00
	2	2517	60			35			205.6	4.40
	3	2517	60			50			205.6	5.20
	4	3020	75			65			205.6	8.30
	5	3020	75			80			205.6	8.90
	6	3020	75			95			205.6	9.80
212	3	2517	60			50			217.6	6.00
224	1	2012	50			20			229.6	3.25
	2	2517	60			35			229.6	5.25
	3	2517	60			50			229.6	6.20
	4	3020	75			65			229.6	11.20
	5	3020	75			80			229.6	12.10
	6	3020	75			95			229.6	13.40
250	1	2012	50			20			255.6	3.80
	2	2517	60			35			255.6	5.80
	3	2517	60			50			255.6	6.55
	4	3020	75			65			255.6	9.70
	5	3020	75			80			255.6	10.50
	6	3020	75			95			255.6	11.70



SPA V-Pulley (taper-lock)

Pulley (dw)	Grooves	Bush	d2 Max	Type	L	b	d3	d1	d	App. Kg
280	1	2012	50			20			285.6	4.70
	2	2517	60			35			285.6	6.40
	3	2517	60			50			285.6	8.90
	4	3020	75			65			285.6	10.40
	5	3535	90			80			285.6	15.10
	6	3535	90			95			285.6	16.70
315	1	2012	50			20			320.6	4.90
	2	2517	60			35			320.6	7.50
	3	3020	75			50			320.6	11.80
	4	3020	75			65			320.6	15.50
	5	3535	90			80			320.6	17.30
	6	3535	90			95			320.6	18.90
355	1	2012	50			20			360.6	5.50
	2	2517	60			35			360.6	8.80
	3	3020	75			50			360.6	12.20
	4	3020	75			65			360.6	13.50
	5	3535	90			80			360.6	20.20
	6	3535	90			95			360.6	21.00
400	1	2012	50			20			405.6	5.91
	2	2517	60			35			405.6	9.35
	3	3020	75			50			405.6	13.32
	4	3020	75			65			405.6	15.45
	5	3535	90			80			405.6	22.09
	6	3535	90			95			405.6	24.25
450	1	2012	50			20			455.6	6.77
	2	2517	60			35			455.6	10.62
	3	3020	75			50			455.6	15.11
	4	3020	75			65			455.6	17.94
	5	3535	90			80			455.6	24.65
	6	3535	90			95			455.6	27.31
500	2	2517	60			35			505.6	12.11
	3	3020	75			50			505.6	17.09
	4	3020	75			65			505.6	20.07
	5	3535	90			80			505.6	27.33
	6	3535	90			95			505.6	30.55
630	2	3020	75			35			635.6	17.80
	3	3020	75			50			635.6	22.68
	4	3535	90			65			635.6	31.17
	5	3535	90			80			635.6	35.31
	6	4040	100			95			635.6	47.72
800	3	3535	90			50			805.6	34.76
	4	3535	90			65			805.6	41.11
	5	4040	100			80			805.6	54.54
	6	4040	100			95			805.6	59.75
1000	3	3535	90			50			1005.6	45.99
	4	4040	100			65			1005.6	63.94
	5	4545	110			80			1005.6	76.41
	6	4545	110			95			1005.6	85.40

SPB V-Pulley (taper-lock)

Pulley (dw)	Grooves	Bush	d2 Max	Type	L	b	d3	d1	d	App. Kg
80	1	1108				25			87	0A
80	2	1108				44			87	0A
80	3	1210				63			87	0A
95	1	1610				25			102	0a
95	2	1610				44			102	0A
100	1	1610				25			107	0.88
	2	1610				44			107	1.30
	3	1610				63			107	1.80
106	1	1610	42							0A
	2	1610	42							0A
	3	1610	42							0A
112	1	1610				25			119	1.21
	2	1610				44			119	1.72
	3	1610				63			119	2.29
118	1	1610				25			125	1.40
	2	1610				44			125	1.94
	3	1610				63			125	2.55
125	1	1610				25			132	1.63
	2	2012				44			132	2.07
	3	2012				63			132	2.73
	4	2012				82			132	3.39
	5	2012				101			132	4.05
132	1	1610				25			139	1.87
	2	2012				44			139	2.40
	3	2012				63			139	3.11
	4	2012				82			139	3.82
	5	2012				101			139	4.20
140	1	1610				25			147	2.16
	2	2012				44			147	2.81
	3	2012				63			147	3.56
	4	2517				82			147	4.85
	5	2517				101			147	4.49
	6	2517				120			147	5.53
150	1	1610				25			157	2.55
	2	2012				44			157	3.34
	3	2517				63			157	4.10
	4	2517				82			157	6.26
	5	2517				101			157	5.73
	6	2517				120			157	6.56
160	1	1610				25			167	2.97
	2	2012				44			167	3.92
	3	2517				63			167	4.70
	4	2517				82			167	5.78
	5	2517				101			167	6.67
	6	3020				120			167	6.20
170	1	1610				25			177	3.42
	2	2012				44			177	4.62
	3	2517				63			177	5.30
	4	2517				82			177	6.71
	5	3020				101			177	6.76
	6	3020				120			177	7.71



SPB V-Pulley (taper-lock)

Pulley (dw)	Grooves	Bush	d2 Max	Type	L	b	d3	d1	d	App. Kg
180	1	1610	42			25			187	3.90
	2	2517	60			44			187	5.62
	3	2517	60			63			187	6.91
	4	2517	60			82			187	7.68
	5	3020	75			101			187	7.89
	6	3020	75			120			187	8.91
	8	3020	75			158			187	12.21
190	1	2012	50			25			197	4.12
	2	2517	60			44			197	6.50
	3	2517	60			63			197	8.10
	4	2517	60			82			197	8.71
	5	3020	75			101			197	9.08
	6	3020	75			120			197	10.16
	8	3030	75			158			197	14.11
200	1	2012	50			25			207	4.64
	2	2517	60			44			207	7.53
	3	2517	60			63			207	9.31
	4	3020	75			82			207	9.38
	5	3020	75			101			207	10.58
	6	3020	75			120			207	11.78
	8	3535	90			158			207	15.22
212	1	2012	50			25			219	5.31
	2	2517	60			44			219	8.56
	3	2517	60			63			219	9.90
	4	3020	75			82			219	10.89
	5	3020	75			101			219	12.17
	6	3535	90			120			219	15.35
224	1	2012	50			25			231	6.01
	2	2517	60			44			231	9.60
	3	2517	60			63			231	11.30
	4	3020	75			82			231	12.48
	5	3020	75			101			231	13.89
	6	3535	90			120			231	18.02
	8	3535	90			158			231	20.75
236	1	2012	50			25			243	6.76
	2	2517	60			44			243	10.62
	3	2517	60			63			243	7.72
	4	3020	75			82			243	14.16
	5	3535	90			101			243	19.39
	6	3535	90			120			243	20.84
250	1	2012	50			25			257	7.68
	2	2517	60			44			257	6.70
	3	3020	75			63			257	12.60
	4	3020	75			82			257	16.08
	5	3535	90			101			257	22.77
	6	3535	90			120			257	24.31
	8	3535	90			158			257	27.39

SPB V-Pulley (taper-lock)



Pulley (dw)	Grooves	Bush	d2 Max	Type	L	b	d3	d1	d	App. Kg
280	1	2012	50			25			287	4.13
	2	2517	60			44			287	7.53
	3	3020	75			63			287	10.74
	4	3020	75			82			287	13.40
	5	3535	90			101			287	19.15
	6	3535	90			120			287	21.04
300	1	2012	50			25			307	0A
	2	2517	60			44			307	8.14
	3	3020	75			63			307	11.64
	4	3020	75			82			307	14.92
	5	3535	90			101			307	20.67
	6	3535	90			120			307	22.75
315	2	2517	60			44			322	8.66
	3	3020	75			63			322	12.21
	4	3535	90			82			322	19.81
	5	3535	90			101			322	21.75
	6	3535	90			120			322	23.98
355	2	3020	75			44			362	11.74
	3	3020	75			63			362	14.24
	4	3535	90			82			362	15.50
	5	3535	90			101			362	23.46
	6	3535	90			120			362	27.75
	8	3535	90			158			362	31.60
400	2	3020	75			44			407	13.87
	3	3535	90			63			407	18.60
	4	3535	90			82			407	23.15
	5	3535	90			101			407	26.63
	6	3535	90			120			407	29.36
450	2	3020	75			44			457	14.00
500	2	3020	75			44			507	18.12
	3	3535	90			63			507	24.70
	4	3535	90			82			507	32.92
	5	3535	90			101			507	39.08
	6	4040	100			120			507	48.28
630	2	3020	75			44			637	27.66
	3	3535	90			63			637	37.20
	4	3535	90			82			637	43.62
	5	4040	100			101			637	53.11
	6	4040	100			120			637	61.62
	8	4545	110			158			637	59.86
800	3	3535	90			63			807	52.39
	4	4040	100			82			807	65.80
	5	4040	100			101			807	74.87
	6	4545	110			120			807	89.49
	8	4545	110			158			807	109.62

PULLEYS

| Bearings & Power Transmission Pty Ltd | www.bpt.net.au



SPC V-Pulley (taper-lock)

Pulley (dw)	Grooves	Bush	d2 Max	Type	L	b	d3	d1	d	App. Kg
150	1	2012	50			25			159.6	0A
200	3	2517	60			85			209.6	10.41
	4	3020	75			110.5			209.6	11.57
	5	3535	90			136			209.6	14.38
	6	3535	90			161.5			209.6	16.13
	8	3535	90			212.5			209.6	16.93
212	3	3020	75			85			221.6	11.35
	4	3020	75			110.5			221.6	13.22
	5	3535	90			136			221.6	16.98
	6	3535	90			161.5			221.6	18.85
	8	3535	90			212.5			221.6	22.59
224	2	3020	75			59.5			233.6	10.97
	3	3020	75			85			233.6	12.97
	4	3535	90			110.5			233.6	17.72
	5	3535	90			136			233.6	19.71
	6	3535	90			161.5			233.6	21.71
	8	3535	90			212.5			233.6	25.69
236	3	3020	75			85			245.6	14.67
	4	3535	90			110.5			245.6	20.49
	5	3535	90			136			245.6	22.60
	6	3535	90			161.5			245.6	24.72
	8	3535	90			212.5			245.6	28.94
250	3	3020	75			85			259.6	16.76
	4	3535	90			110.5			259.6	23.91
	5	3535	90			136			259.6	26.16
	6	3535	90			161.5			259.6	28.42
	8	3535	90			212.5			259.6	32.93
265	3	3535	90			85			274.6	25.04
	4	3535	90			110.5			274.6	21.11
	5	3535	90			136			274.6	23.52
	6	3535	90			161.5			274.6	26.01
	8	3535	90			212.5			274.6	30.91
280	3	3535	90			85			289.6	19.55
	4	3535	90			110.5			289.6	22.23
	5	3535	90			136			289.6	24.91
	6	3535	90			161.5			289.6	27.60
	8	3535	90			212.5			289.6	32.84
300	3	3535	90			85			309.6	21.01
	4	3535	90			110.5			309.6	23.95
	5	3535	90			136			309.6	26.89
	6	3535	90			161.5			309.6	29.83
	8	4040	100			212.5			309.6	49.93
	10	4545	110			263.5			309.6	54.00
315	3	3535	90			85			324.6	22.04
	4	3535	90			110.5			324.6	25.18
	5	3535	90			136			324.6	28.32
	6	3535	90			161.5			324.6	31.45
	8	4040	100			212.5			324.6	44.28
	10	4545	110			263.5			324.5	60.00

SPC V-Pulley (taper-lock)



Pulley (dw)	Grooves	Bush	d2 Max	Type	L	b	d3	d1	d	App. Kg
335	3	3535	90			85			344.6	22.60
	4	3535	90			110.5			344.6	27.60
	5	3535	90			136			344.6	31.11
	6	3535	90			161.5			344.6	34.62
	8	4040	100			212.5			344.6	47.97
	10	4545	110			263.5			344.6	81.00
355	3	3535	90			85			364.6	26.01
	4	3535	90			110.5			364.6	29.44
	5	3535	90			136			364.6	33.23
	6	3535	90			161.5			364.6	37.02
	8	4040	100			212.5			364.6	51.05
	10	4545	110			263.5			364.6	85.00
375	3	3535	90			85			384.6	25.10
	4	3535	90			110.5			384.6	30.72
	5	3535	90			136			384.6	35.84
	6	4040	100			161.5			384.6	46.39
	8	4545	110			212.5			384.6	59.70
	10	4545	110			263.5			384.6	92.00
400	3	3535	90			85			409.6	28.14
	4	3535	90			110.5			409.6	33.24
	5	3535	90			136			409.6	38.32
	6	4040	100			161.5			409.6	50.20
	8	4545	110			212.5			409.6	63.87
	10	5050	125			263.5			409.6	73.00
425	3	3535	90			85			434.6	28.75
	4	3535	90			110.5			434.6	33.76
	5	3535	90			136			434.6	45.51
	6	4040	100			161.5			434.6	56.22
	8	4545	110			212.5			434.6	64.97
	10	5050	125			263.5			434.6	105.00
450	3	3535	90			85			459.6	30.39
	4	3535	90			110.5			459.6	35.90
	5	4040	100			136			459.6	47.85
	6	4545	110			161.5			459.6	58.92
	8	5050	125			212.5			459.6	73.99
	10	5050	125			263.5			459.6	94.00
475	3	3535	90			85			484.6	32.46
	4	3535	90			110.5			484.6	38.41
	5	4040	100			136			484.6	50.60
	6	4545	110			161.5			484.6	61.46
	8	5050	125			212.5			484.6	77.64
	10	5050	125			263.5			484.6	125.00
500	3	3535	90			85			509.6	34.52
	4	3535	90			110.5			509.6	41.06
	5	4040	100			136			509.6	53.49
	6	4545	110			161.5			509.6	64.69
	8	5050	125			212.5			509.6	81.31
	10	5050	125			263.5			509.6	111.00



SPC V-Pulley (taper-lock)

Pulley (dw)	Grooves	Bush	d2 Max	Type	L	b	d3	d1	d	App. Kg
530	3	3535	90			85			539.6	36.82
	4	4040	100			110.5			539.6	50.27
	5	4040	100			136			539.6	62.18
	6	4545	110			161.5			539.6	73.77
	8	5050	125			212.5			539.6	85.60
	10	5050	125			263.5			539.6	145.00
560	3	3535	90			85			569.6	39.41
	4	4040	100			110.5			569.6	53.43
	5	4545	110			136			569.6	65.72
	6	5050	125			161.5			569.6	77.67
	8	5050	125			212.5			569.6	90.90
	10	5050	125			263.5			569.6	121.00
630	3	4040	100			85			639.6	52.10
	4	4545	110			110.5			639.6	66.03
	5	5050	125			136			639.6	79.30
	6	5050	125			161.5			639.6	87.39
	8	5050	125			212.5			639.6	102.88
	10	5050	125			263.5			639.6	130.00
800	3	4545	110			85			809.6	72.00
	4	5050	125			110.5			809.6	90.77
	5	5050	125			136			809.6	102.46
	6	5050	125			161.5			809.6	113.65
	8	5050	125			212.5			809.6	136.55
	10	5050	125			263.5			809.6	170.00
1000	4	5050	125			110.5			1009.6	117.11
	5	5050	125			136			1009.6	133.59
	6	5050	125			161.5			1009.6	149.80
	8	5050	125			212.5			1009.6	181.35
	10	5050	125			263.5			1009.6	230.00

SPZ Pulley (taper-lock)



Pulley (dw)	Grooves	Bush	d2 Max	Type	L	b	d3	d1	d	App. Kg
56	1	1008	25			38			54	0.45
	2	1108	28			50			54	0.53
60	1	1008	25			16			64	0.25
	2	1108	28			49			64	0.60
63	1	1108	28			16			67	0.30
	2	1108	28			28			67	0.40
	3	1108	28			40			67	0.16
67	1	1108	28			16			71	0.30
	2	1108	28			28			71	0.42
	3	1108	28			40			71	0.57
71	1	1108	28			16			75	0.40
	2	1108	28			28			75	0.50
	3	1108	28			40			75	0.60
75	1	1108	28			16			79	0.50
	2	1210	32			28			79	0.50
	3	1210	32			40			79	0.60
80	1	1210	32			16			84	0.40
	2	1210	32			28			84	0.50
	3	1210	32			40			84	0.70
	4	1210	32			52			84	0.80
85	1	1210	32			16			89	0.50
	2	1610	42			28			89	0.60
	3	1610	42			40			89	0.80
	4	1610	42			52			89	0.90
90	1	1210	32			16			94	0.70
	2	1610	42			28			94	0.80
	3	1610	42			40			94	0.90
	4	1610	42			52			94	1.20
95	1	1210	32			16			99	0.80
	2	1610	42			28			99	0.90
	3	1610	42			40			99	1.06
	4	1610	42			52			99	1.20
100	1	1210	32			16			104	0.90
	2	1610	42			28			104	1.00
	3	1610	42			40			104	1.20
	4	1610	42			52			104	1.40
106	1	1610	42			16			110	1.10
	2	1610	42			28			110	1.20
	3	1610	42			40			110	1.30
	4	1610	42			52			110	1.70
112	1	1610	42			16			116	1.15
	2	1610	42			28			116	1.30
	3	2012	50			40			116	1.40
	4	2012	50			52			116	1.70
118	1	1610	42			16			122	1.20
	2	1610	42			28			122	1.50
	3	2012	50			40			122	1.60
	4	2012	50			52			122	2.00
125	1	1610	42			16			129	1.30
	2	1610	42			28			129	1.80
	3	2012	50			40			129	2.00
	4	2012	50			52			129	2.30



SPZ Pulley (taper-lock)

Pulley (dw)	Grooves	Bush	d2 Max	Type	L	b	d3	d1	d	App. Kg
132	1	1610	42			16			136	1.50
	2	1610	42			28			136	2.00
	3	2012	50			40			136	2.40
	4	2012	50			52			136	2.70
140	1	1610	42			16			144	1.60
	2	1610	42			28			144	2.40
	3	2012	50			40			144	2.80
	4	2012	50			52			144	3.10
150	1	1610	42			16			154	2.00
	2	2012	50			28			154	2.80
	3	2012	50			40			154	3.40
	4	2517	60			52			154	3.80
160	1	1610	42			16			164	1.70
	2	2012	50			28			164	3.30
	3	2012	50			40			164	3.90
	4	2517	60			52			164	4.60
180	1	1610	42			16			184	2.00
	2	2012	50			28			184	3.00
	3	2012	50			40			184	3.60
	4	2517	60			52			184	6.50
200	1	2012	50			16			204	2.70
	2	2012	50			28			204	3.30
	3	2012	50			40			204	4.00
	4	2517	60			52			204	5.20
224	1	2012	50			16			228	3.00
	2	2012	50			28			228	3.70
	3	2012	50			40			228	4.40
	4	2517	60			52			228	6.00
250	1	2012	50			16			254	2.80
	2	2012	50			28			254	4.00
	3	2012	50			40			254	4.60
	4	2517	60			52			254	7.00
280	1	2012	50			16			284	3.50
	2	2012	50			28			284	4.40
	3	2517	60			40			284	6.40
	4	2517	60			52			284	7.60
315	1	2012	50			16			319	3.80
	2	2012	50			28			319	5.10
	3	2517	60			40			319	7.40
	4	2517	60			52			319	8.60
355	1	2012	50			16			359	4.50
	2	2012	50			28			359	8.40
	3	2517	60			40			359	8.80
	4	2517	60			52			359	9.40
400	1	2012	50			16			404	4.33
	2	2517	60			28			404	6.90
	3	2517	60			40			404	8.65
	4	2517	60			52			404	10.23