

BENTONE NO MELT 2

HEAVY DUTY NON-MELTING GREASE FOR EXTREME ENVIRONMENTS

CODE: 9111

BENTONE NO MELT 2 is a superior quality adhesive, non-melting grease with a high viscosity base oil for use in plain and anti-friction bearings subjected to elevated temperatures and loads. The consistency of the grease remains stable throughout a wide temperature range. Where service is required in excess of 200°C it is recommended that application intervals be more frequent.

Primary Markets: Industrial, automotive, transport earthmoving, forestry, agriculture, mining and marine and many more.

Recommended applications include:

- Chassis
- Universal joints
- Wheel bearings
- Ball and all and roller bearings
- Kilns
- Many other applications requiring no-melt, high temperature grease lubrication.

Summary of Benefits:

- ✓ Highly water resistance
- ✓ Reduced grease leakage tendency
- ✓ Good pumpability
- ✓ Excellent sealing properties in dusty conditions
- ✓ Wide temperature range

Product Size: 450g, 2.5kg, 20kg, 180kg

BENTONE NO MELT 2

HEAVY DUTY NON-MELTING GREASE FOR EXTREME ENVIRONMENTS

CODE: 9111

Typical Characteristics:

Appearance:	Smooth, Brown
NLGI Classification:	2
Thickener:	Organically Modified Clay
Base Oil Viscosity cSt @ 40°C	450cSt
Worked Penetration, 60 Strokes ASTM D-217	265-295
Oil Separation % IP121	1.5
Copper Corrosion IP112	1b
Kg Oxidation Stability IP142 100H @99°C, pressure drop	3.5
Four Ball Weld Load, Min ASTM D1763	225
Dropping Point °C IP112	None

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Safety Data Sheet (SDS) is available for each product. Users should consult the SDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product. The Safety Data Sheet is available at Sterling Lubricants by email: info@sterlinglubricants.com.au